

# Manu-fit

Professional manual tyre changer



*Juste right !*

*No need to fiddle around anymore !*

MFC



MFA



## SIZE APPLICABLE

- For passenger car, motorcycle, quad, scooter, kart, wheelbarrow and lawn mowers tyres, as from 4" to 21"



## SPECIFICATIONS

Manu-fit C (MFC) :

- Length : 65 cm
- Width : 65 cm
- Height : 75 cm
- Weight : 30 kg

Manu-fit A (MFA) :

The Manu-fit A is an accessory for our Opti-fit and Pro-fit automatic tyre-changers when dealing with small wheels

- Length : 65 cm
- Width : 65 cm
- Height : 16 cm
- Weight : 18 kg

## STANDARD EQUIPMENT

- 1 Mounting/dismounting lever
- 3 Supporting axles for the centre bore, as from 12mm
- Standard color: red RAL 3020

## OPTIONS

- RAL color on request
- Customized adaptations

## Accessoire

RB accessory for a wheel without centre bore

**DQN - DU QUESNE**

Quellinstraat 42

B-2018 Antwerp

Belgium

+32 3 201 51 10

info@dqn.be

www.dqn.be



## MFC- MFA common features



The Manu-fit is equipped with a mechanical fixing plate with pre-positioning of the claws. This makes it possible to quickly secure an excellent grip of the wheel at a comfortable work height. With its 4" to 21" capacity, there are not many car, motorcycle, quad, kart ... and even aircraft wheels that are out reach for this little manual tyre-changer.

The different centre axles will provide a stable support adapted to all the centre bores available on the market. In exceptional cases where there is no centre bore "blind wheel", the RB accessory will be particularly useful.

Its mounting/dismounting lever has been completely revised to reduce stress and make it as easy to handle as possible. The "mounting" part is equipped with a profiled knob to roll the bead over the edge of the rim, thus avoiding damage to the lip of the bead. Its "dismounting" part is the same as that of its elder sisters in the range, Opti-fit and Pro-fit, which have been tried and tested in this field.

## MFC- MFA differences



The Manu-fit C is fitted with a leg equipped with a three-step manual bead breaker, which helps to find the correct ratio for an easy bead breaking of wheels up to 9" wide. This leg also includes housings for three supporting axles and the mounting/dismounting lever. These are useful features allowing to keep everything required within reach throughout the process.

The Manu-fit A is to be considered as an accessory to the Opti-fit and the Pro-fit, extending their functions to deal with smaller rims. It is placed directly on the mounting plate, avoiding the clutter of an additional machine.

## SEE ALSO

*Opti-fit*

*Pro-fit*

*Ergo-line*

*New!*

