

Ergo-Lift

Pneumatic wheel lift



SPECIFICATIONS

- For all types of passenger car, delivery van and light commercial vehicle wheels
- Lifts the wheel at the height of 76 cm
- Standard colour: red RAL 3020

TECHNICAL INFORMATION

MAX. TYRE WIDTH	36 cm
MAX. RIM WIDTH	13"
MAX. WHEEL WEIGHT	60 kg
AIR PRESSURE	7 bar
LENGTH	79/60 cm
WIDTH	61 cm
HEIGHT	39/96 cm
WEIGHT	26 kg



Neerveld 9 - 2550 Kontich - België

+32 3 201 51 10 info@dqn.be www.dqn.be





Free!
Choose your
RAL colour

Ergo-Line



The Ergo-Lift is the first link in the "Ergo-Line" chain. This automatic wheel lift can load your "Ergo-Roll" roller conveyor at a lightening pace or bring the wheel to the load height of all DQN products.


Two configurations are possible: in the "**Ergo-Roll table load**" mode, the lift rises to its maximum height without braking, providing the wheel with horizontal speed so that it moves forward on the roller table. The speed is adjustable according to the distance it must travel on the table. In the "**Machine load**" mode the lift stops at loading height and stays in a high position as long as the wheel has not been unloaded.

The self-activating lift starts to operate as soon as a wheel is placed on it and drops as soon as it is unloaded.


Its semi-circular movement offers the great advantage of moving the wheels from a vertical position (on the ground) to a horizontal position (at work height) without a shock or fall.

The unique compact structure drops completely after the wheel is unloaded. (Height at rest 39 cm)

TWO CONFIGURATIONS



1 Ergo-Roll table load



2 Machine load

OPTIONS

- RAL colour on request
- Customized adaptations